



US005156159A

United States Patent [19]

[11] Patent Number: **5,156,159**

Lampotang et al.

[45] Date of Patent: * **Oct. 20, 1992**

[54] **CO₂ DIAGNOSTIC MONITOR WITH RUPTURABLE CONTAINER**

[75] Inventors: **Samsun Lampotang; Joachim S. Gravenstein; Nikolaus Gravenstein; Michael J. Banner; Dietrich Gravenstein**, all of Gainesville, Fla.

[73] Assignee: **University of Florida**, Gainesville, Fla.

[*] Notice: The portion of the term of this patent subsequent to May 29, 2007 has been disclaimed.

[21] Appl. No.: **505,689**

[22] Filed: **Apr. 9, 1990**

Related U.S. Application Data

[63] Continuation-in-part of Ser. No. 255,400, Oct. 11, 1988, Pat. No. 4,928,687.

[51] Int. Cl.⁵ **A61M 16/00**

[52] U.S. Cl. **128/719; 128/207.14**

[58] Field of Search **128/716, 719, 630, 772, 128/204.22, 205.23, 207.14, 200.26; 412/61; 236/133**

[56] References Cited

U.S. PATENT DOCUMENTS

2,136,236	4/1936	Draper	128/719
2,638,096	5/1953	Waldhaus	
2,890,177	6/1959	Kilmer	
3,114,610	12/1963	Gafford et al.	
3,507,623	4/1970	McConnaughey	
3,659,586	5/1972	Johns	128/716
4,011,859	3/1977	Frankenberger	128/719
4,155,358	5/1979	McAllister et al.	
4,269,194	5/1981	Rayburn	128/719
4,326,515	4/1982	Shaffer et al.	
4,423,739	1/1984	Passaro	128/719
4,428,907	1/1984	Heijenga et al.	

4,538,606	9/1985	Whited	
4,607,643	8/1986	Bell et al.	
4,632,119	12/1986	Reichstein	
4,647,541	3/1987	Guagagno et al.	422/61
4,691,701	9/1987	Williams	
4,723,543	2/1988	Beran	128/719
4,728,499	3/1988	Fehder	
4,740,475	4/1988	Paul	
4,790,327	12/1988	Despotis	128/719
4,879,999	11/1989	Leiman et al.	128/207.14
4,928,687	5/1990	Lampotang et al.	
5,005,572	4/1991	Raemer	128/205.23

Primary Examiner—**Kyle L. Howell**
Assistant Examiner—**Robert L. Nasser, Jr.**
Attorney, Agent, or Firm—**Kerkam, Stowell Kondracki & Clarke**

[57] ABSTRACT

A diagnostic monitor checks the carbon dioxide (CO₂) content of a gas exiting a patient during endotracheal or esophageal intubation. A plurality of composition portions substantially change color in response to exposure to the carbon dioxide. The composition portions change color in response to different times of exposure to carbon dioxide. A magnifying or condensing lens may be positioned on the monitor to enhance viewing of the color change. The monitor may advantageously be made part of an intubation system through which the gases from a patient exit the patient. The differences in time of exposure needed to cause the color change may be accomplished by using semipermeable membranes having differing thicknesses, CO₂ permeabilities, and/or surface areas with each membrane corresponding to a particular one of the composition portions. An arrangement is provided whereby the monitor is automatically activated by the normal assembly steps of a patient breathing circuit.

25 Claims, 10 Drawing Sheets

