

S005599303A

United States Patent [19]

Melker et al.

[11] Patent Number:

5,599,303

[45] **Date of Patent:**

Feb. 4, 1997

[54]	IV	ADMINISTR	ATION	APPARATUS
------	----	-----------	-------	------------------

[76] Inventors: Richard Melker, 6101 NW. 19th Pl., Gainesville, Fla. 32605; Eric J. Hulsman, 1006 Countryside La., Smyrna, Ga. 30080; Brad D. Wellington, 887 Westmont Dr.,

Asheboro, N.C. 27203

[21]	Appl. No.: 344,829	
[22]	Filed: Nov. 21, 1994	
[51]	Int. Cl. ⁶ A61M 5	5/14
[52]	U.S. Cl. 604/80 ; 604/	246
[58]	Field of Search 604/80, 9,	30,
	604/65, 81, 122, 246, 251, 253, 254, 2	
	260, 407; 73/861; 116/273, 264, 274,	275

[56] References Cited

	U.S. PAT	TENT DOCUMENTS	
1,574,460	2/1926	Williamson	116/275
3,251,335	5/1966	Dannevik	116/275
3,797,480	3/1974	Williams	128/726
3,949,737	4/1976	Nielsen	128/726
4,187,847	2/1980	Loeser	604/246
4,287,775	9/1981	Hutton	128/726
4,389,901	6/1983	Lake.	
4,694,161	9/1987	Sackett .	
4,801,106	1/1989	Kawakami et al	242/159
5,059,173	10/1991	Sacco .	
5,343,763	9/1994	Nielsen et al	

5,370,683 12/1994 Fontaine 606/198

Primary Examiner—Corrine M. McDermott Assistant Examiner—N. Kent Gring

Attorney, Agent, or Firm-Saliwanchik & Saliwanchik

[57] ABSTRACT

The subject invention is a novel apparatus for the administration of intravenous fluids. The invention is particularly well suited for accurately and efficiently administering intravenous fluids over a wide range of flow rates. Disclosed is an intravenous fluid administration apparatus having at lease one flow line capable of administering fluid at high flow rates and comprising an airless, dripless, fluid monitoring chamber. A preferred embodiment comprises a main flow line which diverges into at least two flow limbs, where one flow limb is a low-flow limb and another flow limb is a high-flow limb, each having separate flow indicators, and with the flow limbs typically converging into a common tube for fluid delivery to the patient. The subject invention also discloses a novel flow meter, which is particularly well suited for measuring and indicating flow rates over a wide range, without the introduction of air bubbles into the fluid flow being measured. The novel flow meter of the subject invention comprises an elastic displaceable member in a housing, whereby the relative position of the displaceable member, as effected by the amount of force exerted on the displaceable member by the fluid being measured, indicates the flow rate of the fluid.

21 Claims, 4 Drawing Sheets

